

NOVA R680E



Industrial PC for Machine Control

Thanks to its numerous connections, including 10 USB ports and 4 LAN ports as well as two PCIe slots, the NOVA can be used in a wide range of applications in the fields of machine learning or big data. In addition to a temperature range from -10°C to +50°C, the system also has a wide range power input from 8V to 48V.

Technical Data

System

CPU	Intel® Core i5-12500T (FCLGA1700, 6 cores)
CHIPSET	Intel® R680E
GPU	Intel® UHD Graphics 770 (integrated) Nvidia® RTX A2000 (12GB DDR6), Nvidia® RTX 2000 (16GB DDR6), Nvidia® RTX 4000 (20GB DDR6) (optional)
RAM	16 GB SO-DDR5 (optionally up to 64GB)
SSD / HDD	512 GB M.2 PCIe 4.0 NVMe (optional up to 2TB) 2 x 2.5" SATA3 SSD/HDD

I/Os

Front	1 x DC-IN via PIN + Phoenix Plug 4 x 2.5 Gbps LAN RJ45 GbE 2 x HDMI 2.0 // 4096x2340@60Hz 2 x DisplayPort 1.4a // 4096x2340@60Hz 2 x COM RS232 2 x COM RS232/422/485 1 x MIC-In 1 x LINE-Out 8 x USB 3.2 Gen 2x1 1 x GPIO 8-bits (4 x GPI; 4 x GPO), 5~35V, isolation 1.5KV
Back	2 x USB 3.2 Gen 1x1

Environment / Mass

Dimensions (W x D x H)	217 mm x 127 mm x 240 mm
Ambient temperature (operation)	-10° to +50°C
Cooling	passive at 0.7 m/s air flow rate
Idle power consumption in W	25

Environment / Mass

Wall bracket	included
--------------	----------

Extensions

M.2	KeyM 2280 (occupied)
-----	----------------------

PCIe	2 x (x16 slot with x8 connection each)
------	--

Miscellaneous

Operating system	Windows 10 / 11 / Linux
------------------	-------------------------

PSU	8V – 48V DC Power Input
-----	-------------------------

Standards & Certificates	CE, FCC Class A, RCM, BSMI, VCCI, UKCA, IC, IEC 62368: CE(LVD) / BSMI
--------------------------	---

Special features	The temperature range changes with an additional GPU.
------------------	---

Class A warning	The device is intended for use in industrial environments. Operation of this device may cause radio interference in residential areas.
-----------------	--

Warning for 802.11a use	If you want to use the WLAN module according to 802.11a in the 5 GHz range: Use in the 5150 MHz – 5350 MHz frequency range is only permitted indoors!
-------------------------	---