

## BRICK Silver



### Industrial PC with optional DIN rail

Thanks to the optional DIN rail bracket, our BRICK Silver can be used for more than just applications in control cabinets. Thanks to a variety of other interfaces, low power consumption and fanless cooling, the system is also suitable for a wide range of industrial applications.

#### Technical Data

##### System

CPU	Intel® Pentium® Silver J5040 (FCBGA1090, 4 cores)
GPU	Intel® UHD Graphics 605
RAM	8 GB SO-DDR4
SSD / HDD	250 GB SATA SSD

##### I/Os

Front	1 x PowerButton 4 x USB 3.0 2 x Gigabit-LAN 2 x COM RS232 / 422 / 485 1 x VGA 1 x HDMI 2.0 1 x LINE-Out
Back	1 x DIN rail bracket
Sides	2 x COM RS232 / 422 / 485 1 x DIO

##### Environment / Mass

Dimensions (W x D x H)	62.6 mm x 62.6 mm x 160 mm
Ambient conditions (operation)	0°C to +50°C
Cooling	passive
Idle power consumption in W	7

##### Extensions

M.2	KeyM 2280 KeyE 2230
-----	---------------------

## Miscellaneous

Operating system	Windows 10 / 11
PSU	9V – 36V / 1.8 – 7.2A
Standards & Certificates	CE
Class A warning	The device is intended for use in industrial environments. Operation of this device may cause radio interference in residential areas.
Warning for 802.11a use	If you want to use the WLAN module according to 802.11a in the 5 GHz range: Use in the 5150 MHz – 5350 MHz frequency range is only permitted indoors!