

KUMO VI



Digital signage PC with Nvidia RTX3060

The KUMO VI is equipped with an Intel® Core i5-11400H processor and an Nvidia RTX 3060. This mini PC is the perfect companion for power-hungry digital signage applications. Applications in the fields of virtual reality, artificial intelligence and machine learning are also a breeze for the KUMO VI.

Technical Data

General

CPU	Intel® Core i5-11400H
Applications	Digital signage, multi monitor
Idle power consumption in W	44
Ambient conditions	0°C up to +35°C
Cooling	active

Power supply

DC In	19.5V / 17A
Input voltage power supply unit	100 – 240V

Connections

Video output	HDMI 2.1, DisplayPort 1.4a
HDMI 2.1	2
DisplayPort 1.4a	2
Audio output	1x Line-Out, 1x Mic-In
Thunderbolt 4	1
Gigabit LAN	1
2.5 Gigabit LAN	1
USB 3.1 Gen 2	5
2.5? drive	1
SD card	SD/SDHC/SDXC card

Dimensions

Height	61 mm
Width	208 mm

Dimensions

Depth	204 mm
Wall bracket	yes

Graphic

Dedicated graphics	Nvidia RTX 3060
VRAM	6 GB GDDR6
Independent screens	4
Video resolution	7690x4320 @ 60Hz (8K)

Miscellaneous

Operating system	Windows 11 Professional, Windows 10 IoT Enterprise 2021 LTSC Value
Class A warning	The device is intended for use in industrial environments. Operation of this device may cause radio interference in residential areas.
Warning for 802.11a use	If you want to use the WLAN module according to 802.11a in the 5 GHz range: Use in the 5150 MHz – 5350 MHz frequency range is only permitted indoors!