NOVA R680E





Powerful industrial PC for machine control, AI & data-intensive applications

The NOVA R680E is a powerful industrial PC that has been specially developed for demanding applications such as machine control, machine learning and big data. Thanks to its enormous variety of connections with 10 USB ports, 4 LAN interfaces and two PCIe slots, the system can be flexibly expanded and individually adapted to a wide range of application scenarios. The wide-range current input from 8V to 48V and the extended temperature range from -10°C to +50°C also make the NOVA R680E ideal for continuous industrial operation under challenging conditions.

Technische Daten

To the white paper „AI at the Edge“!

System

CPU	Intel® Core i3-14100 (standard) / Intel® Core i5-14400 / i7-14700 (optional)
CHIPSET	Intel® R680E
GPU	Intel® UHD Graphics (integrated) Nvidia® RTX A2000 (12GB DDR6), Nvidia® RTX 2000 (16GB DDR6), Nvidia® RTX 4000 (20GB DDR6) (optional)
RAM	16 GB SO-DDR5 (optional up to 64GB)
SSD / HDD	512 GB M.2 PCIe 4.0 NVMe (optional up to 2 TB) , 2 x 2.5? SATA3 SSD/HDD

I/Os

Front	1 x DC-IN via PIN + Phoenix plug 4 x 2.5 Gbps LAN RJ45 GbE 2 x HDMI 2.0 // 4096×2340@60Hz 2 x DisplayPort 1.4a // 4096×2340@60Hz

spo-comm GmbH
Otto-Kraus-Strasse 4c
D-90411 Nürnberg

Telefon : +49 (0) 911 / 23 98 37 - 0
Fax : +49 (0) 911 / 23 98 37 - 19
E-Mail: info@spo-comm.de

Vertretung durch
Geschäftsführer
Sporrer Michael

Do you need consultation?
vertrieb@spo-comm.de
+49 (0) 911 - 23 98 37 - 0

I/Os

	2 x COM RS232 2 x COM RS232/422/485 1 x MIC-In 1 x LINE-Out 8 x USB 3.2 Gen 2×1 1 x GPIO 8-bits (4 x GPI; 4 x GPO), 5~35V, isolation 1.5KV
Back	2 x USB 3.2 Gen 1×1

Environment / Mass

Dimensions (W x D x H)	217 mm x 127 mm x 240 mm
Ambient temperature (operation)	-10° to +50°C
Cooling	passive at 0.7 m/s air flow rate
Idle power consumption in W	25
Wall bracket	inclusive

Extensions

M.2	KeyM 2280 (occupied)
PCIe	2 x (x16 slot with x8 connection each)

Miscellaneous

Operating system	Windows 10 / 11 / Linux
PSU	8V – 48V DC Power Input
Standards & Certificates	CE, FCC Class A, RCM, BSMI, VCCI, UKCA, IC, IEC 62368: CE(LVD) / BSMI
Special features	The temperature range changes with an additional GPU.
Class A warning	The device is intended for use in industrial environments. Operation of this device may cause radio interference in residential areas.
Warning for 802.11a use	If you want to use the WLAN module according to 802.11a in the 5 GHz range: Use in the 5150 MHz – 5350 MHz frequency range is only permitted indoors!

spo-comm GmbH
Otto-Kraus-Strasse 4c
D-90411 Nürnberg

Telefon : +49 (0) 911 / 23 98 37 - 0
Fax : +49 (0) 911 / 23 98 37 - 19
E-Mail: info@spo-comm.de

Vertretung durch
Geschäftsführer
Sporrer Michael

Do you need consultation?
vertrieb@spo-comm.de
+49 (0) 911 - 23 98 37 - 0